



DVC240XR and DVR240XR

Digital Video Broadcast Modulator and Demodulator



DVC240XR MODULATOR HIGHLIGHTS

- ▶ Circuit Card Assembly
- ▶ DVB-S2 (EN 302 307) to 45 Msps / 190 Mbps
- ▶ DVB-S (EN 300 421) to 68 Msps / 119 Mbps
- ▶ DVB-DSNG (EN 301 210) to 68 Msps / 238 Mbps
- ▶ CCM, VCM & ACM Support in DVB-S2
- ▶ QPSK, 8-PSK, 16-QAM, 16-APSK, 32-APSK Operation
- ▶ Frequency-Agile 50 to 90, 100 to 180, and 950 to 2050 MHz
- ▶ Monitor Port Available
- ▶ Web Browser, SNMP or terminal management
- ▶ Upgrades: Compact Flash or FTP Ethernet
- ▶ FAST Features upgrades available
- ▶ BUC 10 MHz available

DVB MODULATOR

The DVC240XR is a full featured DVB-S2, DVB-DSNG and DVB-S modulator offered as a circuit card assembly or CCA. It runs at data rates from 1 to 238 Mbps and is capable of CCM, VCM and ACM operation.

Selections are available for both 70/140 MHz and L-Band operation with a separate monitor port. The unit is intended for integration into a customer provided chassis for DSNG, enterprise and interactive services. The 254 W x 305 D x 20 H mm card easily fits into a 1 RU chassis and consumes less than 30 Watts.

Integrators and encoder manufacturers find the DVC240XR ideal for applications where a CCA best suits their needs. It permits simple integration of a modulator into a chassis or combining an encoder and modulator into a single unit.

DVR240XR DEMODULATOR HIGHLIGHTS

- ▶ DVB-S , DVB-DSNG and DVB-S2 Ready
- ▶ DVB-S2 (EN 302 307) to 45 Msps / 160 Mbps
- ▶ DVB-S / DSNG (EN 301 210) to 45 Msps / 145 Mbps
- ▶ CCM, VCM & ACM Support in DVB-S2
- ▶ QPSK, 8-PSK, 16-QAM and Q/8/16-APSK (DVB-S2)
- ▶ Dual L-Band Inputs
- ▶ LNB Voltage
- ▶ Upgrades via Reflash
- ▶ TTL Monitor and control

DVB DEMODULATOR

The DVR240XR DVB Broadcast Demodulator Front-End Card is a 45 Msps universal solution for DVB-S DVB-DSNG and DVB-S2 applications in a compact 160 D x 100 W x 14 H mm circuit card assembly or CCA. The small demodulator single CCA solution provided by the DVR240XR is architected with versatile a Field Programmable Gate Array (FPGA) and ASIC technology.

The frequency range of both dual L-Band inputs, from 950 to 2150 MHz, is compatible with standard commercial low-noise block down converters (LNBs). The unit supports LNB voltage and allows user selection of the L-Band input port with LNB voltage. The DVR240XR demodulates DVB-S, DVB-DSNG or DVB-S2 Constant Code and Modulation (CCM). The DVB-S2 mode supports Variable Coding and Modulation (VCM) or the most advanced technology Adaptive Coding and Modulation (ACM). Demodulation of standard MPEG transport stream, raw baseband frames, or a generic transport stream is available.

DVC240XR DVB Modulator and DVR240XR DVB Demodulator

DVC240XR MODULATOR SPECIFICATIONS

IF Interface

Tx IF:	50 to 90 / 100 to 180 MHz (70/140 MHz) 950 to 2050 MHz L-Band
IF Step Size:	100 Hz
Frequency Stability:	3 ppm
Power Output:	0 to -25 dBm, -20 dB at L-Band Monitor
Power Step Size:	0.1 dB
Power Output Accuracy:	± 1.0 dB over temp / frequency
Power Output Stability:	± 0.5 dB over 24 hours
Carrier Mute:	-55 dB
Spurious:	-55 dBc, In-Band -45 dBc, Out-of-Band
IF Impedance and Connector:	75 Ohm (70/140 MHz), BNC-F 50 Ohm (L-Band), SMA-F Monitor (L-Band), Type F-F
Return Loss:	13 dB (70/140 MHz) 7 dB (L-Band), Monitor not specified
Phase Noise:	1 kHz -73 dBc 10 kHz -83 dBc 100 kHz -100 dBc 1 MHz -120 dBc
External Reference:	1, 2, 5, 10 MHz better than ±1 ppm, 1.5 to 10 V _{p-p} , 50 Ohms
Rolloff	20%, 25% or 35%

Baseband (DVB-S, DVB-DSNG) Per ETSI EN 301-210

Data Rate In 1 bps Steps:	1 to 238, within symbol rate limit
Symbol Rate:	1 to 68 Msps
Code Rates:	QPSK 1/2, 2/3, 3/4, 5/6, 7/8 8-PSK 2/3, 5/6, 8/9 16-QAM 3/4, 7/8

Baseband (DVB-S2) Per ETSI EN 302 307

Data Rate:	1 to 190 Mbps, 1 bps steps within symbol rate limits
Symbol Rate:	1 to 45 Msps
DVB Modes:	CCM, ACM, VCM
Terrestrial Framing:	188 (1 Sync Byte, 187 Payload Bytes)
Frame Type:	64800 bits normal, 16200 bits short
Code Rates:	QPSK: 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 8-PSK: 2/3, 3/4, 3/5, 5/6, 8/9, 9/10 16-APSK: 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 32-APSK: 3/4, 4/5, 5/6, 8/9, 9/10

Interface, Physical & Power

Unit Management:	Serial RS-485 / RS-232 (Terminal), Ethernet 10/100 BaseT Web Browser SNMP v1 and v2
Data Interface	Parallel TTL, HE 10 50 connector
Weight:	1.5 pounds (0.68 kg)
Size:	10 W x 12 D x 0.8 H inches 254 W x 305 D x 20 H mm
Power	+5, +12, -12 VDC <30W

Options (Contact Sales)

Mod. & Symbol Rate:	Various S, DSNG, S2 and Symbol Rates
IF Combinations	70/140 MHz, L-Band, L-Band Monitor
BUC Reference	10 MHz 1.5x10 ⁻⁸ stability
Special Modes	ACM / VCM

DVR240XR MODULATOR SPECIFICATIONS

IF Interface

Rx IF:	950 to 2150 MHz
IF Step / Acq Range:	100 Hz / Symbol rate dependent
Input Level:	C0+10 log (Symbol Rate), C0: -130 dBm/Hz to 105 dBm/Hz -70 to -45 dBm @ 1 Msps -60 to -35 dBm @ 10 Msps -53 to -28 dBm @ 45 Msps
Composite Power:	< -20 dBm total input power
LNB Power:	18, 24 VDC or OFF, 350 mA max
Rx Input:	75 Ohm, 7 dB Return Loss, Type F-F
Rolloff	20%, 25% or 35%
Dual Rx IF Input:	Selectable one at a time

Baseband (DVB-S, DVB-DSNG) Per ETSI EN 301-210

Data Rate In 1 bps Steps:	1 to 145 Mbps, within symbol rate limit
Symbol Rate:	2 to 45 Msps
Code Rates:	QPSK 1/2, 2/3, 3/4, 5/6, 7/8 8PSK 2/3, 5/6, 8/9 16QAM 3/4, 7/8

Baseband (DVB-S2) EN 302 307

Data Rate In 1 bps Steps:	2 to 160 Mbps within symbol rate limit
Symbol Rate:	2 to 45 Msps
DVB Modes:	CCM, ACM, VCM
Code Rates (LDPC):	QPSK: 1/2, 2/3, 3/4, 3/5, 4/5, 5/6, 8/9, 9/10 8-PSK: 2/3, 3/4, 3/5, 5/6, 8/9, 9/10 16-APSK: 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
Terrestrial Framing:	204, 188, 187
Internal Clock Stability:	±10 ppm per EN50083
Spectral Inversion:	Auto, normal or inverted

Interface, Physical & Power

Unit Management:	Async serial TTL link
Data Interface	Parallel TTL, HE 10 50 connector
Weight:	0.5 pounds (0.68 kg)
Size:	4 W x 6 D x 0.6 H inches 160 D x 100 W x 14 H
Power	5 VDC <12W
Upgrade	Flash

Options (Contact Sales)

Mod. & Symbol Rate:	Various S, DSNG, S2 and Symbol Rates
Special Modes	ACM / VCM

Environmental For Modulator Or Demodulator

Operating Temperature:	0 to 50°C
Operating Humidity:	Up to 95%, Non-Condensing
Storage Temperature:	-20 to 70°C
Storage Humidity:	Up to 99%, Non-Condensing



2114 West 7th Street, Tempe, Arizona 85281 USA Voice 1 480 333 2200 Fax 1 480 333 2540 Email sales@comtechefdata.com

Comtech EF Data reserves the right to change specifications of products described in this document at any time without notice and without obligation to notify any person of such changes. Information in this document may differ from that published in other Comtech EF Data documents. Refer to the website or contact Customer Service for the latest released product information.